

Technical Data:					
	Basket [Ø/H/loading] [mm/mm/kg]	Rotational Speed [min-1]	Heating Capacity [kVA]	Voltage [V/Hz]	Dimensions W x D x H [mm]
TZ 5	180/120/2	550-1400	0,8	230/50	470x400x580
TZ 10	270/190/5	700-1100	2,1	230/50	700x500x950
TZ 25	380/250/15	500-800	4,1	400/50	710x690x1100
TZ 30	220/180/10	500-1400	1,3	230/50	475 x 630 x 915
TZ 100	430/280/50	300-1000	3	400/50	670 x 900 x 1035



Deburring - Rounding - Grinding - Smoothing - Polishing



Centrifugal dryer
for spotless drying of workpieces after vibratory finishing

Centrifugal Dryer TZ 5, TZ 10 and TZ 25

for drying bulk goods

- solid centrifuge housing made of steel sheet
- cover and water-bearing areas in stainless steel
- mesh feet, height-adjustable, vibration-reducing and fixable
- rotor for holding baskets
- variable speed control
- thermostatically adjustable hot air temperature
- safety lock of the centrifuge cover
- time switch 1 - 60 min
- filter bags



Bulk materials as well as sensitive parts can be dried in the centrifugal dryer
Special versions of baskets, sieves and adapter on request

Centrifugal Dryer TZ 30 and TZ 100

for drying bulk goods, especially for sensitive workpieces

- case made of durable coated steel with lid of stainless steel and service cover on the front side (no attachment on the floor required)
- rotor for the accommodation of baskets
- adjustable rotation speed
- thermostatic regulation of temperature
- electronic standstill surveillance
- safety lock of centrifuge lid
- timer



larger centrifugal dryers on request